Xerox® WorkCentre® 5865/5875/5890 Multifunction Printer

WorkCentre 5800 series multifunction systems are powered by the Xerox® ConnectKey™ Controller. These simple-to-implement systems give you real, practical solutions that easily streamline how you communicate, process and share important information, simplify complex paper-driven tasks, and drive down costs while keeping your data secure.

Convenience Stapler and Work Surface
High Capacity Feeder
Office Finisher (5865/5875 only)
Booklet Maker for Office Finisher
Post Process Inserter
High Volume Finisher (HVF)
C / Z Fold Unit for HVF
Booklet Maker for HVF

System Specifications	WorkCentre 5865	WorkCentre 5875	WorkCentre 5890
Speed (up to) 8.5 x 11 in. / A4 (LEF) 8.5 x 13 to 8.5 x 14 in. / A4 to B4 (SEF) 11 x 17 in. / A3 (A3 SEF) (Bypass Tray will reduce speed by 10 to 20%)	 65 ppm 49 ppm 42 ppm	 75 ppm 49 ppm 42 ppm	 90 ppm 54 ppm 47 ppm
Monthly Duty Cycle[1]	Up to 250,000 pages	Up to 300,000 pages	Up to 400,000 pages
Recommended Average Monthly Print Volume[2]	25,000 to 110,000 pages	30,000 to 125,000 pages	50,000 to 150,000 pages
Hard Drive / Processor / Memory	160 GB / 1 GHz Dual-core / 2 GB system		
Connectivity	10/100/1000Base-T Ethernet, High-Speed USB 2.0 direct print, Optional Wi-Fi (with Xerox® USB Wireless Adapter)		
Controller Features	Unified Address Book, Remote Control Panel, Online Support, Configuration Cloning		
Copy and Print			
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Print: Up to 4800 x 1200, 256 shades of gray		
First-print-out Time	As fast as 2.9 seconds		
First-copy-out Time	As fast as 2.9 seconds from the Platen / 5.9 seconds from the Automatic Document Feeder		
Page Description Languages	Adobe® PostScript® 3™, PDF, PCL® 5c / PCL 6, XML Paper Specification (XPS®) (Optional)		
Print Features	Print from USB, Earth Smart Driver Settings, Job Identification, Booklet Creation, Store and Recall Driver Settings, Bi-directional Status, Scaling, Job Monitoring, Xerox® PrintBack		
Mobile Printing	Apple® AirPrint™, Xerox® Mobile Print® (Optional), Xerox® Mobile Print Cloud® (Optional)		
Scan			
Standard Features	Scan to Network, Scan to Email, Scan to Folder, Scan to SMB or FTP, Text Searchable PDF, PDF/A, XPS, Linearized PDF, JPEG, TIFF, Scan to USB Memory Device, Single Touch Scanning, TWAIN Support		
Optional Features	ConnectKey for SharePoint®, ConnectKey Share to Cloud, Xerox® Scan to PC Desktop® SE and Professional, numerous solutions available through various Xerox® Business Innovation Partners		
Fax			
Standard Features	Internet Fax, Fax Build Job, Network Server Fax Enablement (solutions available through various Xerox® Business Innovation Partners)		
Optional Features	Fax Forward to Email or SMB, Walk-up Fax (one-line and two-line options, includes LAN Fax)		
Security			
Standard Features	McAfee® Embedded, McAfee ePolicy (ePO) Compatible, HDD Overwrite, 256-bit Encryption (FIPS 140-2 compliant), Common Criteria Certification (ISO 15408) (pending), Secure Print, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Identity Services Engine (ISE) Integration, Network Authentication, SSL, SNMPv3, Audit Log, Access Controls, User Permissions		
Optional Features	McAfee Integrity Control, Xerox Secure Access Unified ID System® with Follow-You Printing®, Smart Card Enablement Kit (CAC/PIV/.NET)		

Go to **www.xerox.com/connectkey** for more information about the Xerox® ConnectKey™ Controller.

Xerox® WorkCentre® 5865/5875/5890

Accounting				
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax)			
Optional Features	Equitrac Office®, Equitrac Professional®, YSoft® SafeQ®, other network accounting solutions available through various Xerox® Business Innovation Partners			
Device Specifications				
Control Panel Languages	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian or Romanian, Catalan			
Accessories				
Optional	High Capacity Feeder (HCF) HCF Kit (Letter/Legal SEF) (HCF required) HCF Kit (Tabloid SEF) (HCF required) Envelope Tray (Replaces Tray 2) Office Finisher (optional with 5865/5875 only) Office Finisher with Booklet Maker (optional with 5865/5875 only) Hole Punch for Office Finisher (optional with 5865/5875 only) High Volume Finisher High Volume Finisher with Booklet Maker Z Fold / C Fold Unit (with High Volume Finisher with Booklet Maker) Post Process Inserter (with High Volume Finisher with Booklet Maker) Convenience Stapler (includes Work Surface) Smart Card Enablement Kit Xerox Secure Access Unified ID System® (with USB Card Reader) with Follow-You Printing® Walk up Fax (One- or Two-line options, includes LAN Fax) ScanFlowStore® Xerox® USB Wireless Adapter McAfee® Integrity Control Enablement Kit XPS Print Option Kit			
Foreign Device Interface (FDI) (Optional)	Also known as Auxiliary Access Device, this is an interface to third party access control devices, such as coin machines and card readers.			
Electrical Requirements				
North America	Voltage : 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 5%, 10 A			
Europe	Voltage : 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 5%, 16 A			
Power Consumption	**WorkCentre 5865**	**WorkCentre 5875**	**WorkCentre 5890**	
Running (Average)	1,550 watts	1,600 watts	1,650 watts	
Standby Mode	310 watt			
Low Power Mode	≤160 watts			
Sleep mode	≤4 watts			
Ready to Scan and Print (from Power On)	<230 seconds (3 minutes, 50 seconds)			
Recovery from Low Power	<4 seconds			
Recovery from Sleep	<28 seconds			
Operating Environment				
Required Temperature Range	50° to 90° F (10° to 32° C)			
Required Relative Humidity	15% to 85%			
Sound Power Levels	Operating 7.2 B(A), Standby: 5.0 B(A)		Operating 7.3 B(A), Standby: 5.0 B(A)	
Sound Pressure Levels	Operating: 57 dB(A), Standby: 35 dB(A)		Operating: 58 dB(A), Standby: 35 dB(A)	
Dimensions and Weight	**Width**	**Depth**	**Height**	**Weight**
Base Configuration with OCT	39.0 in. / 990 mm	25.6 in. / 650 mm	43.5 in. / 1,104 mm	271.8 lbs. / 123.3 kg
With Office Finisher (5865/5875 only)	47.6 in. / 1,209 mm	25.6 in. / 650 mm	43.5 in. / 1,104 mm	329.6 lbs. / 149.5 kg

With Office Finisher with Booklet Maker (5865/5875 only)	47.6 in. / 1,209 mm	25.6 in. / 650 mm	43.5 in. / 1,104 mm	364.9 lbs. / 165.5 kg
With High Volume Finisher	64.8 in. / 1,645 mm	25.6 in. / 650 mm	45.1 in. / 1,145 mm	425.1 lbs. / 192.8 kg
With High Volume Finisher with Booklet Maker, C Fold / Z Fold Unit and Post Process Inserter	78.5 in. / 1,995 mm	25.6 in. / 650 mm	46.5 in. / 1,180 mm	485.7 lbs. / 220.3 kg
High Capacity Feeder	15.3 in. / 389 mm	20.1 in. / 510 mm	22.6 in. / 510 mm	66.1 lbs. / 30 kg
Work Surface (Does not add to overall width if combined with High Capacity Feeder	11.2 in. / 285 mm	–	–	–
Certifications				
	FCC Class A Compliant (US), ICES Class A Compliant (Canada) CSA Listed (UL 60950-1, Second Edition) CB Certified (IEC 60950-1, Second Edition) ENERGY STAR® GOST NOM Blue Angel Environmental Choice CE Marked Common Criteria (IEEE 2600.2 standard) (pending) EPEAT GS Mark Citrix® Certified WHQL MEDITECH Cerner			
Paper Handling				
Single-pass Automatic Document Feeder				
Capacity[3]	200 sheets			
Speed (Black-and-white and color)	Up to 105 images per minute (ipm) (simplex) Up to 200 ipm (duplex)			
Paper Sizes Sensed	4.9 x 5.4 in. to 11.7 x 17 in. / 125 x 138 mm to 297 x 432 mm			
Weights	13 lb. bond to 43 lb. bond / 50 gsm to 160 gsm			
Bypass Tray				
Capacity[3]	100 sheets			
Sizes	Custom sizes: 4.25 x 5.5 in. to 11 x 17 in. / A6 to A3			
Weights	16 lb. bond to 80 lb. cover / 60 to 216 gsm			
Types	Bond Carbonless Card Stock Envelopes Hole punched Index Labels Letterhead Plain Preprinted Recycled Transparencies Tabs			

Trays 1 and 2	
Capacity[3]	500 sheets each
Sizes	Custom Sizes from 5.5 x 8.5 in. LEF to 11 x 17 in. SEF / A5 to A3
Weights	16 lb. bond to 53 lb. bond / 60 to 200 gsm
Types	Bond Card Stock Glossy Hole punched Index Labels Letterhead Lightweight Card Stock Plain Preprinted Recycled Tabs
High Capacity Tandem Tray	
Capacity[3]	Tray 3: 1,600 sheets Tray 4: 2,000 sheets
Sizes	Standard Sizes: 8.5 x 11 in. LEF / A4
Weights	16 lb. bond to 53 lb. bond / 60 to 216 gsm
Types	Bond Card Stock Glossy Hole punched Index Letterhead Lightweight Card Stock Plain Preprinted Recycled
High Capacity Feeder (HCF) (Optional)	
Capacity[3]	4,000 sheets Optional HCF Kits: 2,000 sheets with Letter/Legal HCF Kit or 2,000 sheets with Tabloid SEF HCF Kit (Optional)
Sizes	8.5 x 11 in. / A4 LEF Optional HCF Kits: 8.5 x 11 in. / A4 or 11 x 17 in. / A3
Weights	16 lb. bond to 58 lb. bond / 60 to 216 gsm
Types	Bond Card Stock Hole punched Index Letterhead Plain Preprinted Recycled
Envelope Tray (Optional - Replaces Tray 2)	
Capacity[3]	Up to 50 envelopes
Sizes	#10 Commercial (9.25 x 4.125 in.), #9 Commercial (8.875 x 3.875 in.), Monarch, DL, C5
Weights	20 lb. bond to 24 lb. bond / 75 to 90 gsm
Total Capacity	
Device Total Capacity[3]	8,700 sheets

Finishing	
Offset Catch Tray (OCT) (Standard on 5865/5875; not available with 5890)	
Capacity	Up to 300 sheets of 20 lb. bond / 80 gsm
Office Finisher (Optional with 5865/5875 only)	
Top Tray Capacity **Stacking Tray Capacity**	250 sheets unstapled of 80 gsm 2,000 sheets unstapled of 80 gsm or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4)
Top Tray Sizes **Stacking Tray Sizes**	4.25 x 5.85 in. to 11 x 17 in. / A6 to A3 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3
Weights	16 lb. bond to 58 lb. bond / 60 to 216 gsm
Multiposition Stapling	50 sheets of 20 lb. bond / 80 gsm
Hole Punch (Optional) North America: Europe:	 2-3 Hole Punch 2-4 Hole Punch
Office Finisher with Booklet Maker (Optional with 5865/5875 only)	
Top Tray Capacity **Stacking Tray Capacity**	250 sheets unstapled of 80 gsm 2,000 sheets unstapled of 80 gsm or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4)
Top Tray Sizes **Stacking Tray Sizes**	4.25 x 5.85 in. to 11 x 17 in. / A6 to A3 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3
Weights	16 lb. bond to 58 lb. bond / 60 to 216 gsm
Multiposition Stapling	50 sheets of 20 lb. bond / 80 gsm
Hole Punch (Optional) North America: Europe:	 2-3 Hole Punch 2-4 Hole Punch
Booklet Making Capacity[3]	40 booklets (2-15 sheets per booklet – 20 lb. / 80 gsm or less)
Booklet Making Sizes	Letter – 8.5 x 11 in. / A4 SEF Legal – 8.5 x 14 in. / B4 SEF Ledger – 11 x 17 in. / A3 SEF
Saddle-stitch Stapling	2-15 sheets / 8-60 page booklet 16 lb. bond to 24 lb. bond / 60 to 90 gsm
Score / Crease	1-15 sheets / unstapled
High Volume Finisher (HVF) (Optional)	
Capacity[3]	Top Tray – 250 sheets Stacking Tray – 3,000 sheets
Sizes	4.25 x 5.5 in. / to 11 x 17 in. / A6 to A3 / 105 x 148 mm to 297 x 420 mm
Weights	16 lb. to 57 lb. bond / 80 lb cover / 60 to 216 gsm
Stapling[3]	100 sheets Single (any corner), dual, front, rear, SEF and 4-stitch
Hole Punch (Optional) North America: Europe:	 3-hole punch 2-hole Legal punch 2-hole punch 4-hole punch and 4-hole “Swedish” punch
High Volume Finisher with Booklet Maker (Optional)	
Capacity[3]	Top Tray – 250 sheets Stacking Tray – 3,000 sheets
Sizes	4.25 x 5.5 in. to 11 x 17 in. / A6 to A3 / 105 x 148 mm to 297 x 420 mm
Weights	16 lb. to 57 lb. bond / 80 lb. cover / 60 to 216 gsm
Stapling[3]	100 sheets Single (any corner), dual, front, rear, SEF and 4-stitch

Hole Punch (Optional) North America: Europe:	 3-hole punch 2-hole Legal punch 2-hole punch 4-hole punch and 4-hole "Swedish" punch
Booklet Maker Capacity[3]	Tray stop up: 30 booklets (1-15 sheets per booklet) Tray stop down: Unlimited
Booklet Maker Sizes	Letter – 8.5 x 11 in. / A4 / 210 x 297 mm Legal – 8.5 x 14 in. / 216 x 356 mm Ledger – 11 x 17 in. / A3 / 297 x 420 mm
Booklet Maker Weights	16 lb. to 57 lb. bond / 80 lb. cover / 60 to 216 gsm
Saddle-stitch Stapling[3]	Saddle-stitch (2-15 sheets / 8-60 page booklet)
Folding	V-folding (1-15 sheets / unstapled)
Z Fold / C Fold Unit (Optional with HVF with Booklet Maker)	
Capacity[3]	50 sheets or unlimited capacity with tray stop in the down position
Sizes	Letter – 8.5 x 11 in. / A4 / 210 x 297 mm
Weights	16 lb. to 57 lb. bond / 80 lb. cover / 60 to 216 gsm
Post Process Inserter (Optional with HVF and HVF with Booklet Maker)	
Capacity[3]	250 sheets
Sizes	Letter – 8.5 x 11 in. / A4 / 210 x 297 mm Legal – 8.5 x 14 in. / 216 x 356 mm Ledger – 11 x 17 in. / A3 / 297 x 420 mm
Weights	16 lb. to 57 lb. bond / 80 lb. cover / 60 to 216 gsm
Convenience Stapler (Optional - Includes Work Surface)	
Capacity[3]	50-sheet stapling 5,000 staples Requires a separate power outlet
Copy	
First-copy-out Time	2.9 seconds from the Platen / 5.9 seconds from the Single-pass Automatic Document Feeder
Sides (input:output)	1-1, 1-2, 2-2, 2-1
Quantity	1 to 9,999
Resolution (max.)	Up to 600 x 600 dpi
Reduction / Enlargement	Variable zoom from 25% to 400% in 1% increments
Concurrency	Program-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)
Copy Features	Annotation and Bates™ stamping (with color capability and font size adjustment) Authentication for Services Auto Paper Select Auto Reduction & Enlargement to fit selected paper size Auto Tray Switching Automatic 2-sided / Duplex Booklet Creation Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Stapling Transparencies

Xerox® Copier Assistant®	Xerox® Copier Assistant® (XCA) Software provides a PC-based alternative to the user interface touch screen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features. Section 508 compliant. For more information or to download Xerox® Copier Assistant for free, visit **www.xerox.com**
Print	
First-print-out Time	As fast as 6.2 seconds
Print Resolution	Up to 4800 x 1200, 256 shades of gray
Print Features	Application Defaults Banner Sheet Enable / Disable Bi-directional Status Cover Selection Delay Print (specific time) User Permissions Image Options (Toner Saver, Resolution (Standard, High) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) LAN Fax (requires optional Fax Kit) Layout / Watermark (N-up (up to 16 pages per sheet), Multi-up, Booklet layout / finishing, Fit to new paper size) Overlays Paper Selection by Attribute Sample Set Saved Job Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs) TWAIN Print Driver
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TXT
Operating Systems	Microsoft® Windows® XP (32- and 64-bit) Windows Server 2003 (32- and 64-bit) Windows Server 2008 (32- and 64-bit) Windows Server 2012 Windows Vista (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Mac OS 10.5, 10.6, 10.7, 10.8 Solaris® 9, 10 HP-UX® 11v2 IBM® AIX® 5 Redhat® Fedora® Core 15-17 Redhat Enterprise 4 and 5 openSUSE® 11 and 12 Ubuntu® Unix®
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6,WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP Apple® Bonjour® IPv6 Secure FTP Most protocols not in use can be disabled
Administrative Protocols	DHCP, BOOTP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, SSL, NTP, DNS, SSDP
Fonts	PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts
Xerox® Mobile Express Driver® (X-MED)	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network, and X-MED automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.

Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Xerox Secure Access Unified ID System®, Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.
Print Solutions	
Xerox® Mobile Print Cloud (Optional)	Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it.
Xerox® Mobile Print Solution (Optional)	Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or MFP without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.
Scan	
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)
Input Speed	Scan at up to 200 ipm color scanning and black-and-white – 8.5 x 11 in. / A4 LEF
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white), 8-bit (grayscale), 24-bit (color)
Maximum Scan Area	11 x 17 in. / A3
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other MFPs Confirmation sheet options
Network Protocols	sFTP, FTP, SMB, NetWare, HTTP, HTTPS
File Formats	Color TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black-and-white TIFF (G3MH, G4 MMR compression - single or multiple pages) Searchable PDF and PDF/A (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black-and-white and within MRC)) JPEG XPS Encrypted / Password Protected PDF (Network Scan Templates only) Linearized PDF
Document Management Fields (Meta Data)	Features only available in Network Scan to File Templates: • 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations • Customized fields viewed on user interface for variable data input
Scan Features	Mixed Size Originals Scan Build Job Compression Quality / File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Driver Bound Originals Edge Erase Reduction / Enlargement
Supported Scan Destinations (Standard)	Scan to USB Drive Scan to Email Scan to PC / Server Client (SMB or FTP) Scan to Mailbox Scan to Secure FTP and HTTPS Scan to Home Scan to Application

Supported Scan Destinations (Optional)	Xerox® Scan to PC Desktop® (Professional and SE) ScanFlowStore® Xerox® ConnectKey™ for SharePoint Xerox® ConnectKey Share to Cloud Various Xerox® Business Innovation Partner Solutions
Authentication	Supports Kerberos (UNIX / Windows Server) SMB (Windows Server) NDS LDAP Xerox Secure Access Unified ID System® Locally on device (internal database) Convenience Authentication via Magstripe, Proximity and Smart Card (CAC/PIV/.NET) readers
Scan to Email (Standard)	
Directory Access	Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino) Downloaded address list (comma-separated file format)
Scan Features	• Email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options • Scan to Email S/MIME Encryption • Email signing (requires Smart Card option) • Auto send to self
Network Scanning – Software Solutions	
Xerox® Scan to PC Desktop® Professional (Optional)	A desktop offering that provides advanced document imaging, archiving, editing and organization tools: • PaperPort Professional image viewing and file management software – Complete PDF functionality – Secure PDF workflow of all scanning applications • OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion • Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes email inbox polling capability
Xerox® ConnectKey™ for SharePoint® (Optional)	Xerox® ConnectKey for SharePoint simplifies and streamlines the way you scan, capture and store your paper-based documents. Using your Xerox® MFP, you can route documents directly into the precise document repository folder, just like you would from your PC. At the MFP, you can browse to the folder, name the document, and add any key indexing information before you scan. With the flexibility to capture and route to SharePoint as well as Windows folders, ConnectKey is the right solution for any office that needs to archive and share paper-based documents.
Xerox® ConnectKey Share to Cloud (Optional)	Xerox® ConnectKey Share to Cloud provides organizations with powerful, easy and secure document scanning capabilities that connect your Xerox® MFP to popular cloud services and email, such as Google Docs, SalesForce.com, Office 365 and Dropbox™ and gives employees anytime, anywhere access to their most important documents using mobile devices.
Security	
Features	• Expanded Authentication – Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows 2000 / Windows Server 2003 / Windows Server 2008), NDS, LDAP – Xerox® Secure Access – Local Authentication (internal database) – Smart Card authentication -144k CAC / PIV Card Support (2048 bit certificate key) / .NET • Secure Data – Digitally signed PDF (when using Smart Card authentication) – Encrypted Scan to Email – Encrypted / Password Protected PDF (when using Network Scan Templates only) – Secure Print (up to 10 digit PIN or Network Authentication) – Immediate Image Overwrite – On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk – FIPS 140-2 256 bit Hard Disk Encryption • Expanded Authorization – SA access based on network credentials – Authorization per user per service – User Permissions required to access Print and Print Features (e.g. color access, or time restrictions) reflects in the print driver • Secure Network Access • IP Filter, IPsec, IPv6, SSL, SNMPv3, HTTPs, 802.1X, Cisco® TrustSec integration (optional), Device Security – McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, , McAfee Integrity Control (optional) • Common Criteria Certification ISO 15408 (pending)

Xerox Secure Access Unified ID System® (Optional)	Xerox Secure Access Unified ID System integrates your Xerox® multifunction systems with your existing employee/student ID PIN or badge providing a flexible and convenient authentication system. Allow your staff, employees or students to send documents to a centralized print server. Then, at any multifunction printer on the network, they'll simply log in with a swipe of their magnetic or proximity ID card or their PIN to securely print their job. For more information, go to **www.office.xerox.com/software-solutions**
Fax	
Network Server Fax Features	
Compatibility	ITY (CCITT) group 3 Various Xerox® Business Innovation Partner Solutions
Maximum Scan Area	11 x 17 in. / A3
Fax Send Features	One- or two-sided scanning (up to 11 x 17 in. / A3) Add to send list (50 numbers maximum) Build Job, Speed Dial, Delay send (specific time) Original type (photo, text or photo and text)
Fax Print Features	One- or two-sided printing, staple, Secure Print
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi
Internet Fax Features	
Capability	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients
Address Directory Access	Send: Multi-page TIFF, PDF, PDF/A Receive: TIFF, MTIFF, PDF, PDF/A, PS, text, PCL, PRN, JPEG
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white)
Network Protocols	SMTP (send), POP3 (receive)
Compliance	ITU-T T.37 compliant
Walk-up Fax Features (Optional (Customer-installable) – 1 and 2 lines)	
Compatibility	ITU (CCITT) Group 3
Speed / Modems	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time ATA analogue terminal adapter utilizing T38 (optional)
Compression / Speed	MH/G3, MMR/SG3
Resolution	**Walkup Send:** Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi **Receive:** Accepts all sizes
Fax Send Features	LAN Fax (fax from print driver) Auto fax transmission reduction Page-by-page job status at the machine Delay start, Build Job, Favorites Automatic memory resend Automatic cover sheets PSTN Fax Device Address Book (up to 1,000 contacts)
Fax Receive Features	One- or two-sided printing Stapled or unstapled Receive print mode – Manual (size, margin, stock, header) / Auto Output tray selection Up to 200 password protected mailboxes Secure receive Receive timestamp Auto answer delay
Fax Forward	Forward to Email or SMB Location Fax forward on receive only
Fax Reports	Activity, Dial directory, Group directory, Transmission confirmation, Pending fax, Options report, On demand overwrite report, Mailbox report, Broadcast report

Auto Dialing	Speed Dials: 5,000 total (one- or two-line options) Group Dials: Up to 200 groups with up to 400 recipients per group (one- or two-line options) Auto Redial: Up to 14 attempts (per country requirements) • 1 to 25 minute intervals • Batch send (up to memory capacity)
Device Management	
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2
Xerox® CentreWare® Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: • Works with any SNMP-managed printer from any manufacturer. • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. • Requires Windows XP, Vista or Windows 7 and Internet Explorer 6.0 and higher. • CentreWare Integration available for Tivoli® NetView®, Unicenter TNG®, Microsoft Management Console (MMC), HP® OpenView®
Novell NDPS/NEPS	Server gateway application: centralized management tool.
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: • Device monitoring and troubleshooting • Extensive reporting and discovery of new devices • Usage collection, chargeback and billing capabilities
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® printers and MFPs. And as an SAP customer you benefit from having SAP-certified Xerox device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and MFPs are available to download. **www.office.xerox.com/software-solutions**
Xerox® SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAPenvironment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at **www.office.xerox.com/software-solutions**
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction systems by storing Xerox software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at **www.office.xerox.com/software-solutions**
CentreWare Internet Services – Integrated Web Pages Provided by the Device	
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS Output feature selection (2-sided, output color, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12
Support	Install print / scan drivers and online support available via web page
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian, Simplified Chinese, Korean, Japanese
Remote Services	
Xerox® MeterAssistant®	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Xerox® SuppliesAssistant®	Automatically orders supplies for Xerox output devices based on actual usage, eliminating the need to manually manage supplies inventory.
Xerox® MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.

Xerox® WorkCentre® 5865/5875/5890

Accounting			
Xerox® Standard Accounting (Standard)			
Tracking	Copy, Print, Fax and Scan usage		
Accounting	Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department)		
Features	• Administrator can manage the feature via the Web User Interface or device control panel in tools • Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file		
Accounting Options – Network Accounting – Third Party Enablement			
	• Enhanced network accounting with up to the minute data on how the system is being used • Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax • Numerous solutions are available through Xerox® Business Innovation Partners. For details visit **www.xerox.com** • Security enhancements with the addition of HTTPS protocol support • WorkCentre requests account authentication from third party server enabling larger databases of users and accounts • Accept Authentication Login at control panel and pass to third party Networking Account Interface with third party accounting terminal for accounting user interface		
Supplies	**Description**	**Quantity**	**Part Number**
Toner Cartridge	Includes 2 Toner Cartridges and Waste Toner Bottle	110,000 pages[4] (55,000 pages each)[4]	006R01552
Waste Toner Bottle	Supplied with each Toner Cartridge Box	100,000 pages[4]	008R12896
Staple Cartridges	Office Finisher (5865/5875 only)	5,000 per cartridge (15,000 staples)	108R00493
	Office Finisher with Booklet Maker (5865/5875 only)	5,000 per cartridge (15,000 staples)	108R00493
	Office Finisher with Booklet Maker – saddle-stitch stapling (5865/5875 only)	2,000 per cartridge (8,000 staples)	108R01158
	HVF and HVF with Booklet Maker • Complete Cartridge • Refill Cartridge	 5,000 per cartridge 5,000 per cartridge (15,000 staples)	 008R12912 008R12898
	HVF with Booklet Maker – saddle-stitch stapling	2,000 per cartridge (16,000 staples)	008R12897
	Convenience Stapler • Complete Cartridge • Refill Cartridge	 5,000 per cartridge 5,000 per cartridge (15,000 staples)	 008R12964 008R12941
Smart Kits®			
Fuser Module	Includes Ozone Filter	400,000[4]	109R00773
Xerographic Module – Metered		450,000[4]	109R00672
Xerographic Module – Sold	North America: Europe:	450,000[4]	113R00674 113R00673
Document Handler Feeder Rolls		150,000 feeds	113R00718

[1] Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
[2] Expected regular monthly throughput
[3] Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.
[4] Approximate pages. Declared Yield based on 5 page job size, 6% area coverage, using letter / A4 media. Yield will vary based on media size, image area coverage, media orientation and usage patterns.

Our products allow use of papers certified by the FSC, PEFC and SFI, and those made with post consumer recycled content and chlorine-free paper. For more information regarding our entire line of paper and specialty media, contact your Xerox® representative or visit us at **www.xerox.com/supplies**.

Return spent imaging supplies through the Xerox® Green World Alliance collection/reuse/recycling program. For more information, visit **www.xerox.com/about-xerox/recycling**.

For more information, call **1-800-ASK-XEROX** or visit us at **www.xerox.com/office**

©2013 Xerox Corporation. All rights reserved. Xerox®, Xerox and Design®, ConnectKey, Copier Assistant®, Global Print Driver®, MeterAssistant®, Mobile Express Driver®, Scan to PC Desktop®, SuppliesAssistant®, WorkCentre® and Xerox Secure Access Unified ID System® are trademarks of Xerox Corporation in the United States and/or other countries. As an ENERGY STAR® partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. The information in this brochure is subject to change without notice. Updated 5/13 W5ZSS-01UD